Gomez Trading Holland B.V.
SERVICE AROUND THE WORLD

Goldhofer

Available NEW Goldhofer THP-SL Axle lines

Price on Request

Details	
Manufacturer	Goldhofer
Type	THP/SL 25 Axle lines with accessories
Year	NEW
Axles	
Axle Brand	BPW Eco Plus
Suspension	Hydraulic pendle
Capacity THP/SL 6	
Maximum axle load	45.000 Kg per axle
Total Axle Load	6x 45.000 Kg = 270.000 Kg
GVW	270.000 Kg
Empty Weight	19.800 Kg
Loading Capacity	250.200 Kg
Measurements THP/SL 6	
Length	13.250 mm
Width	3.000 mm
Height	1.175 mm (+/- 300)
Capacity THP/SL 5	
Maximum axle load	45.000 Kg per axle
Total Axle Load	5x 45.000 Kg = 225.000 Kg
GVW	225.000 Kg
Empty Weight	17.250 Kg
Loading Capacity	207.750 Kg
Measurements THP/SL 5	
Length	13.250 mm
Width	3.000 mm
Height	1.175 mm (+/- 300)
Capacity THP/SL 4	
Maximum axle load	45.000 Kg per axle
Total Axle Load	4x 45.000 Kg = 180.000 Kg
GVW	180.000 Kg
Empty Weight	13.850 Kg
Loading Capacity	166.150 Kg
Measurements THP/SL 4	
Length	10.250 mm
Width	3.000 mm
Height	1.175 mm (+/- 300)

Main features Gooseneck	
Loading Platform (3.700 mm x 2.440 mm)	3,5 Inch 5th Wheel and adjustable steering wedge
Hydraulic Lifting and Lowering	Integrated Lashing Coupling
Lashing Rings	Spare Wheel + Holder
Hydraulic Locking Pin to Connect the Gooseneck	Auto Lube For Gooseneck With Pump, Beka-MA
Coupling height 1.450 mm	Hydraulic supporting cylinders

Capacity THP/SL 3	
Maximum axle load	45.000 Kg per axle
Total Axle Load	3x 45.000 Kg = 135.000 Kg
GVW	135.000 Kg
Empty Weight	10.650 Kg
Loading Capacity	124.350 Kg

Measurements THP/SL 3	
Length	4.500 mm
Width	3.000 mm
Height	1.175 mm (+/- 300)

1 x Low Profile Deck FB 250

8.0000 mm, with mechanically coupling, not traversable.
Payload classification in combination (6+6) 170.000 Kg
Hight 250 mm, length 8.000 mm, width 2.990 mm
Coupling heads at front and at rear for modular

Loading Security

2 pair lashing rings LC 32000 daN at the coupling heads
2 pairs bushings for screw-in lashing rings LC 20000 daN laterally of the rear coupling head
8 pairs bushings for screw-in lashing rings LC 20000 daN laterally in the outer frame
8 pairs bushings for screw-in lashing rings LC 20000 daN on top of the outer frame including 4 units screw-in lashing rings LC 20000 daN

1x extension for low profile deck, 4000 mm
Hight 250 mm
Empty Weight approx. 5.900 Kg

Load security
3 pairs bushings for screw-in lashing rings LC 20000 daN laterally in the outer frame
3 pairs bushings for screw in lashing rings laterally LC 20000 daN on top of the outer frame

1x Extension for low profile deck, 5.000 mm
Hight 250 mm
Empty weight approx. 7.100 Kg

Load Security
4 pairs bushings for screw-in lashing rings LC 20000 daN laterally in the outer frame
4 pairs bushings for screw-in lashing rings laterally LC 20000 daN on top of the outer frame

Gomez Trading Holland B.V.
SERVICE AROUND THE WORLD

Goldhofer

1x Low Profile Deck FB 300

10.000 mm, without mechanically coupling, not traversable
Payload classification in combination (6+6) 300.000 Kg
Hight 300 mm, length 10.000 mm, width 2.990 mm
Coupling heads at front and at rear for modular
Bogies for modular bogie
Empty weight approx. 21.300 Kg

Load security

2 pairs lashing rings LC 32000 daN at the coupling heads
2 pairs bushings for screw-in lashing rings LC 20000 daN laterally of the rear coupling head
10 pairs bushings for screw-in lashing rings LC 20000 daN laterally in the outer frame
10 pairs bushings for screw-in lashing rings LC 20000 daN on top of the outer frame including 4 units screw-in lashing rings LC 20000 daN

Accessories

1x Hydraulic locking pin to connect modular bogies in lengthwise

Available 1x Goldhofer Crawler deck BB 450 A

Capacity

Total Weight	14.400 Kg
Payload	100t / 120t in combination 4+6

Measurements

Length deck	8.000 mm + 5.000 mm
Width	1.350 mm
Thickness	450 mm

Extra Info

At the rear lashing coupling for connection to THP-bogies	In the front claw couplings for connection to gooseneck or claw coupling adapter
Integrated supply lines for hydraulics, brake and electrics with connection couplings	1 pair lashing rings (LC= 30,000 daN) in the rear coupling head
8 pair lashing rings (LC = 20,000 daN) arranged at the outside of the outer beam	Fold out outriggers and inserts on the outer beam (basic length)
Fold out side extensions and mattresses on the inner tube	1x Quick coupling adapter THP/SL to connect the coupling claws of a deck to coupling lashes of a modular bogie or a Gooseneck
1 x Drive on wedge for excavator deck in steel execution (4 pieces) Weight 360 Kg	

Selling Conditions

This quotation is subject to errors and to being unsold. We assume no liability for this specification to be complete, correct, and/or up-to-date.
We can intermediate for all arrangements necessary to transport and ship this equipment when needed. The buyer will be accounted for the costs of transport, shipment, assurance, loading, and offloading at the harbor.
It is understood that the equipment is in the described state and is approved personally or by e-mail.
The equipment is sold without any form of guarantee.
We reserve the right to sell to other clients as long as no prepayments have been received. The price mentioned is stated in euros and payments are to be fulfilled in euros by a bank transaction.

Gomez Trading Holland B.V.

TEL: 0031-572-870040 info@gomeztrading.com 57093245 / NL852435228B01
TEL: 0031-572-870039 www.gomeztrading.com NL852435228 / NL074174676

Gomez Trading Holland B.V.
SERVICE AROUND THE WORLD

Goldhofer





Gomez Trading Holland B.V.

TEL: 0031-572-870040
TEL: 0031-572-870039

info@gomeztrading.com
www.gomeztrading.com

57093245 / NL852435228B01
NL852435228 / NL074174676





Gomez Trading Holland B.V.

TEL: 0031-572-870040
TEL: 0031-572-870039
info@gomeztrading.com
www.gomeztrading.com
57093245 / NL852435228B01
NL852435228 / NL074174676





Gomez Trading Holland B.V.

TEL: 0031-572-870040 info@gomeztrading.com 57093245 / NL852435228B01
TEL: 0031-572-870039 www.gomeztrading.com NL852435228 / NL074174676